

DH-IPC-HFW1239TC1-A-LED

2 MP Entry Full-color Fixed-focal Bullet Network Camera



Series Overview

With features of simple installation, easy operation, and high performance-cost ratio, Dahua Entry series network camera is applicable to small and medium-sized scenes, such as homes/residences, small-sized retail stores, and other small and medium-sized enterprises.

Functions

Smart H.265+ & Smart H.264+

With advanced scene-adaptive rate control algorithm, Dahua smart encoding technology realizes the higher encoding efficiency than H.265 and H.264, provides high-quality video, and reduces the cost of storage and transmission.

Full-color

With high-performance sensor and large aperture lens, Dahua Full-color technology can display clear colorful image in the environment of ultra-low illuminance. With this photosensitivity technology, the camera can capture more available light, and display more colorful image details.

Human Detection

Dahua intelligent algorithms extract moving human targets from videos and filters out alarms that are triggered by non-human targets to increase the accuracy and effectiveness of alarms.

Cyber Security

Dahua network cameras employ a series of security technologies, including security authentication and authorization, access control protocols, trusted protection, encrypted transmission and encrypted storage. These technologies improve the camera's defense against external cyber threats and prevent malicious programs from compromising the device.

- * The parameters and datasheets below can only be applied to 1239-S6 series
- 2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image.
- · Outputs max. 2 MP (1920 × 1080)@25/30 fps.
- · H.265 codec, high compression rate, ultra-low bit rate.
- · Built-in warm light, and the max. illumination distance is 30 m.
- DWDR, 3D NR, HLC, BLC, digital watermarking, applicable to various monitoring scenes.
- ROI, SMART H.264+/H.265+, flexible coding, applicable to various bandwidth and storage environments.
- Abnormality detection: Motion detection, video tampering, audio detection, network disconnection, IP conflict, illegal access.
- · Built in Mic.
- · 12 VDC/PoE power supply, easy for installation.
- · IP67 protection.
- · Supports human detection.













Protection (IP67, Wide Voltage)

IP67: The camera passes a series of strict test on dust and soak. It has dust-proof function, and the enclosure can work normally after soaking in 1 m deep water for 30 minutes.

Wide voltage: The camera allows $\pm 30\%$ (for some power supplies) input voltage tolerance (wide voltage range), and it is widely applied to outdoor environment with instable voltage.

Technical S	Specificatio	n						Main stream: 1920 × 1080@(1–25/30 fps)
Camera					Video Frame Rate	sub stream: $704 \times 576@(1-25 \text{ fps})/704 \times 480@(1-30 \text{ fps})$ *The values above are the max. frame rates of each stream; for multiple streams, the values will be subjected to the total encoding capacity.		
Image Sensor		1/2.8" CMOS					video Frame Nate	
Max. Resolution		1920 (H) × 1080 (V)						
ROM		16 MB					Stream Capability	2 streams
RAM		64 MB				Resolution	1080p (1920 × 1080); 1.3M (1280 × 960); 720p (1280 × 720); D1 (704 × 576/704 × 480); VGA (640 × 480); CIF	
Scanning System		Progressive					(352 × 288/352 × 240)	
Electronic Shutter Speed		Auto/Manual 1/3 s-1/100,000 s					Bit Rate Control	VBR;CBR
Min. Illumination		0.005 lux@F1.6					Video Bit Rate	H.264: 32 kbps–4096 kbps; H.265: 12 kbps–4096 kbps
S/N Ratio		> 56 dB					Day/Night	Color/B/W
Illumination Distance		Up to 30 m (98.43 ft) (Warm light)					BLC	Yes
Illuminator On/Off Control		Auto;Manual					HLC	Yes
Illuminator Number		1 (Warm light)					WDR	DWDR
Angle Adjustment		Pan: 0°–360°; Tilt: 0°–90°; Rotation: 0°–360°					White Balance	Auto; natural; street lamp; outdoor; manual; regional custom
Lens		notation, 0 300					Gain Control	Auto/Manual
Lens Type		Fixed-focal					Noise Reduction	3D NR
Lens Mount		M12					Motion Detection	OFF/ON (4 areas, rectangular)
Focal Length		2.8 mm; 3.6 mm					Region of Interest (RoI)	Yes (4 areas)
Max. Aperture		F1.6					Smart Illumination	Yes
Field of View		2.8 mm: H: 105°; V: 56°; D: 126° 3.6 mm: H: 87°; V: 44°; D: 105°					Image Rotation	$0^{\circ}/90^{\circ}/180^{\circ}/270^{\circ}$ (Support $90^{\circ}/270^{\circ}$ with $1080p$ resolution and lower)
Iris Control		Fixed					Mirror	Yes
		2.8 mm: 0.7 m	n (2.30 ft)				Privacy Masking	4 areas
Close Focus D	istance	3.6 mm: 1.3 m (4.27 ft)					Audio	
	Lens	Detect	Observe	Recognize	Identify		Built-in MIC	Yes, built-in Mic
	2.8 mm	43.9 m (144.03 ft)	17.5 m (57.41 ft)	8.8 m (28.87 ft)	4.4 m (14.44 ft)		Audio Compression	G.711a; G.711Mu; PCM; G.726
	3.6 mm	58.9 m	23.6 m	11.8 m	5.9 m		Alarm	
DORI Distance	*DORI (Detec	ct, Observe, Recognize, Identify) is a standard sy					Alarm Event	Network disconnection; IP conflict; illegal access; motion detection; video tampering; audio detection; security exception; SMD (human)
	(EN-62676-4) for defining the ability of a person viewing the video to distinguish persons or objects within a covered area.						Network	
		in this table do intelligent fun		-			Network Port	RJ-45 (10/100 Base-T)
		ioning manual/project design tool.					SDK and API	Yes
Intelligence Human Detection		Support the classification and accurate detection of					Network Protocol	IPv4; IPv6; HTTP; TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; DHCP; DNS; DDNS; NTP; Multicast; ICMP; IGMP; P2P
Smart Search		human Work together with Smart NVR to perform refine					Interoperability	ONVIF (Profile S & Profile T); CGI
		intelligent search, event extraction and merging to					User/Host	6 (Total bandwidth: 24 M)
Video		event videos					Storage	FTP
video		H.265; H.264; H.264H; H.264B; MJPEG (Only supported					Browser	IE; Chrome; Firefox
Video Compression		by the sub stream)					Management Software	Smart PSS Lite; DSS; DMSS; DoLynk Care
Smart Codec		Smart H.265+; Smart H.264+					Mobile Client	iOS;Android

Entry Series | DH-IPC-HFW1239TC1-A-LED

Cyber Security	Video encryption;Configuration encryption;Digest;WSSE;Account lockout;Security logs;Generation and importing of X.509 certification;HTTPS;Trusted boot;Trusted execution;Trusted upgrade	
Certification		
Certifications	CE-LVD: EN62368-1; CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU;	
Power		
Power Supply	12 VDC/PoE (802.3af)	
Power Consumption	Basic: 1.5 W (12 VDC), 1.6 W (PoE); Max.: 3.4 W (12 VDC), 4.3 W (PoE) (H.265 + intelligence on + WDR+ warm light intensity)	
Environment		
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)	
Operating Humidity	≤95%(RH), non-condensing	
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)	
Storage Humidity	≤95%(RH), non-condensing	
Protection	IP67	
Structure		
Casing Material	Metal + Plastic	

 $W \times H$)

0.29 kg (0.64 lb)

0.40 kg (0.88 lb)

180.4 mm \times 70 mm \times 70 mm (7.10" \times 2.76" \times 2.76") (L \times

Ordering Information					
Туре	Model	Description			
IP CAMERA	DH-IPC-HFW1239TC1-A- LED	2 MP Entry Full-color Fixed-focal Bullet Network Camera			
	G3416GW	G3/4" Water Joint			
	DH-PFA151	Corner mount bracket			
	DH-PFA130-E	Water-proof Junction Box			
	DH-PFA152-E	Pole Mount Bracket			
Accessories (Optional)	DH-PFA134	Junction box			
	DH-PFM321-EN	DC12V1A power adapter			
	DH-PFM321D-EN	DC12V 1A power adapter			
	DH-PFM320D-EN	DC12V2A power adapter			
	PFM900-E	Integrated Mount Tester			

Accessories

Optional:







DH-PFA151 Corner mount bracket

DH-PFA130-E Water-proof Junction Box

DH-PFA152-E Pole Mount Bracket







DH-PFA134 Junction box

DH-PFM321-EN DC12V1A power adapter DC12V 1A power adapter

DH-PFM321D-EN








PFM900-E Integrated Mount Tester

Ceiling Mount	Wall Mount	Pole Mount(Vertical)

Dimensions (mm[inch])

mm [inch]



3-ø4.5 [ø0.18]

Product Dimensions

Net Weight

Gross Weight