

KX-DAi4K8216N3P16

16Channel 1U 16PoE NVR

Design and specifications are subject to change without notice.
Pictures in the document are for reference only, and the actual product shall prevail.

- 16 Channel IP video access
- Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
- Up to 16 Channel perimeter protection
- Up to 4 Channel video stream face recognition
- Up to 24 face pictures/sec processing
- Up to 20 face databases with 100,000 face images in total
- 1-8 PoE Ports support ePoE & EoC



System		Audio and Video	
Main Processor	Multi-core embedded processor	IP Camera Input	16 Channel
Operating System	Embedded LINUX	Two-way Talk	1 Channel Input, 1 Channel Output, RCA
Perimeter Protection			Display
Performance	16 channel, 10 IVS rules for each channel	Interface	1 HDMI, 1 VGA
Object classification	Human/Vehicle secondary recognition for tripwire and intrusion	Resolution	HDMI: 3840 × 2160, 1920 × 1080, 1280 × 1024, 1280 × 720 VGA: 1920 × 1080, 1280 × 1024, 1280 × 720
AI Search	Search by target classification (Human, Vehicle)	Decoding Capability	4-ch@8MP (30fps), 16-ch@1080P (30fps)
Face Recognition			Multi-screen Display
Performance	Max 24 face pictures/sec processing (modeling and comparing)	1/4/8/9/16	
	4 channel video stream face recognition/16 channel picture stream face recognition (with FD camera)		
Stranger Mode	Detect strangers' faces (not in device's face database). Similarity threshold can be set manually.	Recording	
AI Search	Up to 8 target face images search at same time, similarity threshold can be set for each target face image.	Bandwidth	320 Mbps (160 Mbps when AI function enabled)
Database Management	Up to 20 face databases with 100,000 face images in total. Name, gender, birthday, nationality, address, ID information can be added to each face picture.	Compression	Smart H.265+/H.265/Smart H.264+/H.264/MJPEG
Database Application	Each database can be applied to video channels independently.	Resolution	16MP, 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 1.3MP, 720P, D1 etc.
Trigger Events	Buzzer, Voice Prompts, Email, Snapshot, Recording, Alarm Out, PTZ Activation, etc.	Record Mode	Manual, Schedule (Continuous, MD (Motion Detection), Alarm, IVS)
Metadata		Record Interval	1–120 min (default: 60 min), Pre-record: 1–30 sec, Post-record: 10–300 sec
Video Detection and Alarm			
Face	Gender, age, glasses, beard, mask.	Trigger Events	Alarm Out, Video Push, Email, Recording, PTZ, Tour, Snapshot, Voice Prompt, Buzzer and Screen Tips
Vehicle	Vehicle color, vehicle model, vehicle logo, plate color, vehicle decorations, call, seatbelt.	Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Scene Change
Human Body	Tops style, tops color, bottom style, bottom color, hat, bag.	Alarm input	4 Channel
Non-motor Vehicle	Type, color, people number.	Relay Output	2 Channel
Playback and Backup			
AI Search	Support search target video by metadata.	Sync Playback	1/4/9/16
		Search Mode	Time/Date, Alarm, MD and Exact Search (accurate to second)
		Backup Mode	USB Device/Network

KX-DAi4K8216N3P16

16Channel 1U 16PoE NVR

Design and specifications are subject to change without notice.
Pictures in the document are for reference only, and the actual product shall prevail.

Third-party Support	
Third-party Support	Arecont Vision, Airlive, AXIS, Canon, Dynacolor, JVC, LG, Panasonic, Pelco, Xunmei, Samsung, Sanyo, Sony, Watchnet and more
Network	
Interface	1 RJ-45 Ports (10/100/1000 Mbps)
PoE	16 ports (IEEE802.3af/at) 1-8 ports support ePoE & EoC
Network Function	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search (Support KBVISION IP camera, DVR, NVS, etc.), P2P
Max. User Access	128 users
Mobile App	iPhone, iPad, Android
Interoperability	ONVIF 2.4, SDK, CGI
Storage	
Internal HDD	2 SATA III Ports, Up to 8 TB capacity for each HDD
eSATA	N/A
Auxiliary Interface	
USB	2 USB Ports (1 Rear USB 3.0, 1 Front USB 2.0)
RS232	1 Port, for PC Communication and Keyboard
RS485	1 Port, for PTZ Control
Electrical	
Power Supply	Single, AC100V–240V, 50–60 Hz
	NVR: <15.6W (Without HDD)
Power Consumption	PoE: Max 25.5W for single port 130W total rated power, 80% control for protection
Fan	Smart fan, automatically adjust running speed

Environmental	
Operating Conditions	-10°C to +55°C (+14°F to +131°F), 86–106kpa
Storage Conditions	0°C to +40°C (+32°F to +104°F), 30–85% RH
Construction	
Dimensions	1U, 375.0 mm × 327.4 mm × 53.0 mm (14.76" × 12.89" × 2.09")
Net Weight	2.70 kg (6.0 lb) (without HDD)
Gross Weight	4.00 kg (8.8 lb) (without HDD)
Dimensions (mm[inch])	

